

**Component Video & Digital Audio BALUN**

ITEM NO.: CV01A




The Component Video & Digital BALUN is designed for component video signal (Y, Pb, Pr) and one digital audio be transmitted via cost effective one CAT5 UTP cable. Used in pairs, the Component Video/Digital Audio BALUN supports 408i/p, 720p and 1080i/p video formats for hi-definition (HDTV) video application. Application for control rooms, multimedia rooms, communications centers, convention facilities, classroom video corporate projection system.


**Features:**

- Designed for Component video and Digital Audio signal transmission over one CAT5 UTP cable.
- Up to 300 meters for video and 180 meters for Digital audio.
- **Support up to HDTV. ( 480I /480p/720p/1080i)**
- Perfect for DVD, VCR, DVR, TV, Satellite receivers, monitors, home theatre and other equipments supporting component video

**Installation View:**



**Panel View:**




Front View



Rear View

## RJ-45 Jack Pin Define

| RJ - 45 Jack |       |          |
|--------------|-------|----------|
| PIN          | Color | Function |
| 1            | W-O   | Pr +     |
| 2            | O     | Pr-      |
| 3            | W-G   | Pb +     |
| 4            | BL    | Y-       |
| 5            | W-BL  | Y+       |
| 6            | G     | Pb -     |
| 7            | W-BR  | Audio+   |
| 8            | BR    | Audio-   |



## Specification:

| ITEM NO.                    | CV01A   |
|-----------------------------|---|
| VIDEO INPUT (RCA Connector) | Green color for Y, Blue color for Pb, Red color for Pr,                       |
| Audio Input                 | RCA connector x1  |
| Support                     | 480I /480p/720p/1080i   |
| Bandwidth                   | Video: 60Mhz, 3dB roll off, Digital Audio: 25MHz, 1dB roll off                |
| Maximum Input               | 1.0Vp-p , 75 Ohms   |
| Insert Loss video           | 1dB for 0.1Mhz. Gradually increasing to 3.0dB over the frequency range        |
| Insert Loss audio           | Less than 1dB per pair over the frequency range                               |
| Return Loss video           | Greater than 15dB over the frequency range                                    |
| Return Loss audio           | Greater than 15dB over the frequency range                                    |
| Common Mode Rejection video | - 55db max.   |
| Common Mode Rejection audio | - 55db max.   |
| Connector                   | RJ45 for CAT5 cable, 4 RCA connectors for Green (Y), Blue(Pb), Red( Pr),Audio |
| Power                       | X   |
| Distance                    | 180 meters (Max.)   |
| CABLE FOR RJ-45             | Twisted Pair CAT 5 (AWG24)  |
| Temperature                 | Operation: 0 to 55°C, Storage: -20 TO 85°C, Humidity: up to 95%               |
| Dimensions W x H x D mm     | 70*133*44   |
| Weight g                    | 300   |