

FORESIGHT CCTV INC.

10 Leavey Court, North York, On, Canada M2H1E6 Tell: 416-512-6288 Toll: 1-888-GO2-CCTV Fax: 416-225-2889

RS232 TO RS422/485 Bi-Directional Converter

ITEM NO.: RS002, RS0021


RS002 RS232 to RS485/RS422 Bi-Directional Converter Features:

- RS232 Input option: DB9 or RJ11.
- RS485/RS422 output option: terminal or RJ11.
- RS232 to RS485 or RS232 to RS422 conversion.
- Four full Duplex wires: two half duplex wires.
- Switch setting for full duplex or half duplex operation.
- Auto Baud Rate Sensing.
- Supports transfer speeds of up to 115.2Kbps.
- Extends up to 1200 meters (under 100Kbps).
- Support up to 32 units to be set in RS-485 multi drop installations.
- LEDS indications for power and signal status monitoring.
- Over current protection when 2 signals are shortened together at the RS422/485 end.
- Surge Protection 16KV ESD.
- Built in termination resistors.
- Power supply included.

RS002I RS232 to RS485/RS422 Bi-Directional Converter-Isolation


• Identical same as RS002, but without RJ11 output and built in 3KV isolation protection.


Installation View:



Panel View:


RS002





http://www.foresight-cctv.com


RS0021





st duplex	1	2	3	4
FULL	T+	<i>T-</i>	R+	R-
HALF	T/R +	T/R-	X	X

RS002 RJ11/12



RJ11-RS422(OUT)	RJ11-RS485(OUT
1.TX-	1.TX/RX
2.TX+	2.TX/RX
3.X	3.X
4.GND	4.GND
5.RX-	5.
6.RX+	6.

RS232 PIN Assignment				
DCD	Data Carrier Detect			
RXD	Receive Data			
TXD	Transmit Data			
DTR	Data Terminal Ready			
GND	Chassis Ground			
DSR	Data Set Ready			
RTS	Request to Send			
CTS	Clear to Send			
RI	Ring Indicator			
	DCD RXD TXD DTR GND DSR RTS CTS			



Specification:

ITEM NO.	RS002	RS002I			
RS232 Input	RJ11/12 Connector or DB9.	DB9			
RS485/422 Output	Terminal or RJ11/12 Connector	Terminal			
Signal Output	2-wire half-duplex RS485 or 4-wire full-duplex RS485/RS422				
LEDS	TX-RS232(GRN).RX-RS232(GRN	Power(RED), TX-485/422(GRN), RX-1422(GRN), TX-RS232(GRN), RX-RS232(RED),DTS(GRN),RTS(GRN)			
Transmission Range	1200 meter (4000 ft)				
Data Rate	Up to 115.2Kbps				
Operating Temperature	0-65℃				
Operation Mositure	10-90%				
Power Consumption	DC5V 300mA				
Power Supply	DC12V 300mA Regulated				
DIMENSIONS W x H x D mm	108x74x27				

http://www.foresight-cctv.com

2