

FORESIGHT CCTV INC

10 Leavey Court, North York, On, Canada M2H1E6 Tell: 416-512-6288 Toll: 1-888-GO2-CCTV Fax: 416-225-2889

Video Transformer Filter Series


ITEM NO.: CB001VH, TVB001

CB001VH Coaxial BALUN For DVR

- BNC male to BNC female with mini cable 15 on both sides.
- Perfect work with DVR to immunity DVR interference.
- Built in a highly balanced mode of video transmission, which is immune to interference from these, and other sources of noise:
 Data signals, other video signals, nearby power, ringing telephones, fluorescent lights, transformers, and more...

Application and Installation:

Add CB001VH on video receive side (Front of Monitor or DVR) to immunity the Interference, which caused by mismatch of Impedance Matching. If there is still some noise, Then use monitor to check each connecting point (between two wire connection), to find out where is the source of interference, then add one more CB001VH to compensate the Impedance Matching for clear video Image. If you are not able to check where the source of interference is, then add CB001VH on all of wire connection and camera.




TVB001 Twisted Pair VIDEO BALUN

- Eliminate interference under long range cabling caused by "Impedance Matching", add TVB001 BALUN at "connecting point" between two-wire connections for compensation.
- Including 4 pieces UY connectors for connection.

Application and Installation:

Using TTP111VH/TTP414VH/TTA111VH...etc VH Series put at receiver side (Front of Monitor or DVR) to immunity the interference. If the interference can not be cleaned up by VH series, then use monitor to check each connecting point (between two wire connection), to find out where is the source of interference, then add one more TVB001 to compensate the Impedance Matching for clear video Image. If you are not able to check where the source of interference is, then add TVB001 on all of wire connection and camera.



■ SPECIFICATION

ITEMS	CB001VH	TVB001
Cable	Coaxial	Twisted Pair
Cable Connection	BNC male to BNC female	UY connector
Dimensions mm	84x28x21 with 19cmx2 cable	35x25x20 with 12cmx2 cable